



Face Material

Self-adhesive material for plotter. Cast vinyl. Liner that offers superior cuttability with conventional die-cutting and computer sign making systems.

| | |
|-------------------|----------------------------------|
| Type | Cast vinyl |
| Colour and Finish | 54 colours available |
| Weight | 70 g/m ² ±10% ISO-536 |
| Thickness | 50 μ ±10% ISO 534-80 |

Adhesive

Solvent based acrylic permanent adhesive featuring high cohesion and good water resistance. Designed for a wide variety of substrates such as glass, ABS, PS, PVC. Unsuitable for apolar surfaces (like PE and PP).

| | |
|------------------|----------------------------|
| Reference | ASP26 Permanent |
| Type | Acrylic permanent |
| Min. Appl. Temp. | +10°C |
| Service Temp. | -20°C/+130°C |
| Shear | High |
| Tack | Medium N/inch ² |
| Final Adhesion | High N/inch |

Liner

| | |
|-------------------|--|
| Type | One side siliconised clay coated Kraft |
| Colour and Finish | White |
| Weight | 135 g/m ² ±10% PP-032 - ISO 536 |
| Thickness | 145 μ ±10% ISO 534 |
| Transparency | n.a. % DIN 53 147-64 |

Applications

High performance opaque cast vinyl film for use on the toughest applications, including irregular surfaces and substrates with rivets and corrugations. Designed for extended outdoor durability, these films are ideal for high impact recreational vehicles, marine and automotive graphics and striping, fleet graphics, architectural signage, decals, service station markings and computerised sign making. Black and white 10 years outdoor durability; all the other colours and clear 7 years outdoor durability. Durability is given in good faith based on simulated weathering tests and real life vertical exposure in non-extreme mid-European conditions.